



MARVIC GEAR 75W-90

(Marvic Gear 75W-90)

Product Description

This oil for transmissions and differentials conforms to API GL-5, and provides outstanding protection for gears and bearings that are subject to high loads. With the appropriate frictional characteristics for synchromesh mechanisms, it provides a good shift feel with every gear change.

Features

- Excellent load bearing performance
Because this oil conforms to API GL-5, it is suited even for hypoid gear axles, used under high speed impact load and low speed high load conditions.

- Excellent gear durability and wear resistance
An appropriate extreme pressure additive is added to prevent gear scoring (grooves and scratches that occur in the sliding direction) and pitting (damage causing metal fragments to fall off the surface).

- Outstanding foaming prevention performance
Anti-foaming performance is enhanced to prevent seizure, malfunction, and oil leakage due to oil film shortage.

- Excellent corrosion prevention performance
It uses an extreme pressure additive that inhibits corrosion of parts inside the gear casing, even at high temperatures.



Recommendations

- Transmission and differential oil for vehicles that specify XW-90

- | |
|-------------------------|
| ■ MARVIC GEAR 75W-90 |
| ■ Mineral oil |
| ■ SAE viscosity: 75W-90 |
| ■ Standard: API:GL-5 |

Usage Precautions

Be sure to check the recommended viscosity for the vehicle before use.
It is not suitable for vehicle models that specify XW-80.



Typical Properties

Density (15°C g/cm ³)	0.8650
Flash point (°C)	208
Pour point (°C)	-40
Kinematic viscosity (40°C mm ² /s)	85.29
Kinematic viscosity (100°C mm ² /s)	14.14
Viscosity index	171
Copper plate corrosion	1b

Product Packaging and JAN Code

- Package 20L JAN4531291008476
200L drum