Refrigeration oils SUNISO & Sunice





SUNDED

SUNOCO

History

The Founding Sprit of Original "SUN" is always with us.

1886 The beginning of "SUN Spirit" beyond 100 Years

Sun Oil Company (SUNOCO) was established in 1886 in Pennsylvania and with in a few years it became one of the largest multinational oil company.

1927 SUNISO has brought innovation to the refrigeration industry

The history of the refrigeration oils began in 1927, when SUNOCO first developed SUNISO and launched it into the industrial market.

1947 Full-scale launch of SUNOCO products in Japan

Japan Trading Company, the former company of JSO, was established as the exclusive distributor of SUNOCO products in Japan.

1966 JSO started production of SUNISO in Japan

In 1966, Japan Sun Oil Company, Ltd. was established with the investments from SUNOCO, and production of SUNISO began in Japan. JSO was entrusted with the marketing of APAC region and started exporting to Asia since 1969.

1995 SUNOCO (Thailand) Co., Ltd.

SUNOCO (Thailand) Co., Ltd. was established in Bangkok in order to deliver high quality lubricating products to the growing Asian market.

1996 ISO 9001/9002 certification to the plant and R&D department

Ichikawa Plant and the Technical Development Center of JSO were certified for ISO9001/9002 as the first lubricant manufacturer in Japan.

2005 J-SUN Shanghai Trading Company., Ltd.

J-Sun Shanghai Co., Ltd. started technical support service for the SUNISO users in mainland China.

2016 JSO 50th Anniversary

JSO marks the 50th Anniversary. The founding sprit of original "SUN" is always with us for the next 50 years.

Japan Sun Oil Company is the Only Authorized Manufacturer of SUNOCO products in the Asia-Pacific region.

Integrated production from development to manufacturing.



From development at the Technical Development Center to manufacturing at the Ichikawa Plant, we deliver reliable, high quality lubricants to various industries, such as refrigeration oils, process oils, grinding oils, industrial oils, specialty oils and automotive lubricants.

ISO14001 ISO9001

Ichikawa Plant and Technical Development Center have acquired ISO 14001 and ISO 9001 certifications for the purpose of ensuring a stable supply of high quality products, saving resources and energy, quick response to environmental issues, and avoidance of environmental risks in advance.

JSO's unique blending technology "Dry Air Mixing Method".






JSO uses a unique " Dry Air Mixing Method" to minimize the risk of contamination with water and other impurities. This method is very suitable for the production of refrigeration oils.

Ichikawa Plant



- Base Oil Tank : 27 (12,569 kiloliters)

- Drum Filling Capacity : 300 drums/hour
- Pail Filling Capacity : 600 pails/hour



Site Area : About 26,869 square meters

Blending Tank: 9 (Max.20 kiloliters/tank)

Production Capacity 50,000 kiloliters/year

Outdoor Product Tank : 4 (224 kiloliters)

SUNISO & Sunice REFRIGERATION OIL

SUNISO GS/GSD series for HCFC, Natural refrigerants

Products: 3GS, 4GS, 5GS, 3GSD, 4GSD, 5GSD

- ISO VG : VG32, VG56, VG100
- Features: The world's most famous refrigeration oil. For various refrigeration systems using HCFC & natural refrigerants.
- Package : 200L DRUM, 20L PAIL, CARTON CASE (4L x6)



SUNISO 4SA & 4HT for R717 (NH3)

Products: 4SA,4HT

ISO VG : VG56

Features: 4SA & 4HT are both specifically designed for using with R717. Long time trusted history of 4SA and improved high-temperature durability of 4HT is the reason for the customer's choice.

Package : 200L DRUM, 20L PAIL

Sunice SL series for HFC, HFO

Products: SL-10S, 22S, 32S, 46S, 68S, 100S, 120T, 170T, 220T, 320T

- ISO VG : VG10-VG320
- Features : JSO's finest Polyolester (POE) refrigeration oil. For various refrigeration systems using HFC & HFO refrigerants.
- Package : 200L DRUM, 20L PAIL, CARTON CASE (4L x6, 1L x10)



Sunice SL-68SP for Refrigeration Vehicles

Products: SL-68SP

ISO VG : VG68

- Features: Specially formulated Polyolester (POE) refrigeration oil for refrigerated vehicles with the swash-plate compressors.
- Package : 20L PAIL, CARTON CASE (1L x10)

Sunice P46 for Car A/C system with R134a/R1234yf

Products: P46

ISO VG : VG46

Features: JSO's latest Polyalkylene Glycol(PAG) refrigeration oils for car air conditioning systems working with Belt-Driven compressor. Designed to use for either R134a or R1234yf refrigerants.

Package : CARTON CASE (1L x10)

Sunice PB100 for Car A/C system with R134a

Products: PB100

ISO VG : VG100

- Features: JSO's long-selling Polyalkylene Glycol (PAG) refrigeration oils for car air conditioning systems working with Belt-Driven compressor. Good to use in Vane type. Suitable for R134a.
- Package : 200L DRUM, CARTON CASE (1L x12)









SUNISO & Sunice product portfolio

		Product name	ISO VG	Density at 15°C g/cm³	Viscosity 40°C mm²/s	Viscosity 100°C mm²/s	Pour point °C	Flash point (COC) °C
	SUNISO GS series is widely used in various applications. Good for	SUNISO 3GS	32	0.909	29.5	4.3	-40	178
	HCFC and natural refrigerants.	SUNISO 4GS	56	0.915	54.9	6.0	-35	188
SUNISO		SUNISO 5GS	100	0.921	94.6	7.8	-27.5	208
REFRIGERATION OIL No.1 Mineral Ref Oil Brand	SUNISO GSD series has been enhanced antifoaming	SUNISO 3GSD	32	0.910	29.5	4.4	-40	178
JSO is the Only One Authorized Suniso Manufacturer in Asia and Pacific.	properties, so it can be used in chillers that have problems with forming phenomena at startup.	SUNISO 4GSD	56	0.915	54.5	6.1	-35	182
	· · · · · · · · · · · · · · · · · · ·	SUNISO 5GSD	100	0.925	96.5	8.1	-25	188
	SUNISO 4SA & 4HT are specially developed for ammonia	SUNISO 4SA	56	0.902	53.9	6.7	-40	198
	applications.	SUNISO 4HT	56	0.855	54.3	8.2	-35	240
	Sunice SL series is designed specifically for use with	Sunice SL-10S	10	0.928	10.1	2.5	below –50	182
	HFC/HFO refrigerants, developed to meet the performance	Sunice SL-22S	22	0.951	22.5	4.1	below –50	212
Sunice	demands of the refrigeration industry.	Sunice SL-32S	32	0.956	32.3	5.1	-35	230
SYNTHETIC REFRIGERATION OIL		Sunice SL-46S	46	0.955	45.8	6.6	-42.5	228
Designed by JSO Sunice SL series was formerly		Sunice SL-68S	68	0.960	66.6	8.2	-40	254
known as SUNISO SL series. We've changed our brand name of		Sunice SL-100S	100	0.974	98.1	11.2	-35	234
synthetic products to clarify the distinction between mineral products and synthetic products.		Sunice SL-120T	120	0.971	115.8	12.2	-30	272
		Sunice SL-170T	170	0.968	161.0	15.4	-30	280
		Sunice SL-220T	220	0.976	216.0	19.0	-27.5	286
		Sunice SL-320T	320	0.967	310.0	22.6	-15	298
	POE for refrigerated vehicles with R134a/R404A/R410A	Sunice SL-68SP	68	0.963	64.9	8.1	-37.5	266
	PAG for vehicle a/c with R134a & R1234yf	Sunice P46	46	1.012	46.3	9.0	-45	202
	PAG for vehicle a/c with R134a	Sunice PB100	100	1.048	94.8	19.2	-42.5	246

Description

SUNISO can be used in virtually any installation, regardless of compressor or evaporation temperature and are miscible with HCFC refrigerants and natural refrigerants, such as R22, R717,R600a and R290.

SUNISO are refined from specially selected naphthenic crude oils by special method as suring excellent lubricity and other properties. SUNISO is approved by all major airconditioner, refrigerator,freezer, car airconditioner manufacturers in the world.

4SA is a specially formulated naphthenic refrigeration oils optimized for R717 system. 4HT is a highly refined paraffinic refrigeration oil for R717 systems and has improved high temperature durability.

Sunice SL series is synthetic refrigeration oils designed for using into refrigeration compressors for refrigerators, freezers, chillers and industrial refrigeration systems to be charged with HFC/HFO refrigerants. Especially having excellent miscibility and compatibility with HFC refrigerants such as R134a, R404A, R407C, R410A, R507.

Featuring the following characteristics:

- Excellent Hydrolytic Stability
- Remarkable Thermal Stability
- Outstanding Lubricity
- High Electrical Insulating Property.

SL-68SP is developed to reduce wear on swash plate compressors exposed to high pressures.

P46/PB100 is suitable for vehicle a/c using a belt-driven compressor. WARNING : P46/PB100 is not applicable to electric compressors used in a/c on HV and EV.

Oil Selector for SUNISO & Sunice

	Refrig	erant	Evaporator temperature																
	ASHRAE Registration	Oil Type	From (°C)		Piston Con	npressor			Screw Cor	npressor		С	Centrifugal	Compress	sor	<refri vehicle Swash Compr</refri 	Plate	<vehic Belt-dr Compr</vehic 	
	R22	MO	-25℃	3GS	4GS			4GS	5GS										
HCFC	R22	MO	-35℃	3GS	4GS			4GS											
	R22	MO	-30℃	3GS				3GS											
Propane	R290	MO/POE/PAG	-30℃	3GS	4GS	5GS													
Propylene	R1270	MO/POE	-30℃	3GS	4GS	5GS													
Isobutane	R600a	MO/POE	-30℃	3GS	4GS	5GS													
	R717	MO	-30℃	3GS	4GS	4SA	4HT	4GS	4SA	4HT									
NH3(ammonia	R717	MO	-40℃	3GS	4SA			4GS	4SA										
	R717	МО	-50℃	3GS				4GS	4SA										
	R744-sub	POE	-50℃	32S	46S	685													
CO2	R744-trans	POE	-50℃	68S															
	R23	POE	-100℃	325	46S	68S													
HFC	R404A	POE	-50℃	325	46S	68S		68S	100S	170T	220T					68SP			
	R407C	POE	-30℃	68S				170T	220T										
	R410A	POE	-25℃	325				68S	100S							68SP			
	R410A	POE	-45℃	325				170T	220T							68SP			
	R417A	POE	-15℃	68S				170T	220T										
	R448A	POE	-50℃	325	465	685		68S	100S	170T	220T								
	R449A	POE	-50℃	325	46S	685		685	100S	170T	220T								
HFC/HFO	R452A	POE	-40℃	325	465	685		68S	100S	170T	220T								
	R454A	POE	-40℃	325	465	685		685	100S	170T	220T								
	R507	POE	-60℃	325				68S	100S	170T	220T								
	R134a	POE	-20°C	325	465	685		170T	220T			685	100S	170T	220T	68SP		P46	PB
HFC	R134a	POE	-40℃	325	46S			685	100S			68S	100S	170T	220T	68SP		P46	PB
	R245fa	POE	-20℃					685	100S	170T	220T	685	100S	170T	220T				
	R1234yf	POE	-20℃	325	465	685		685	100S	170T	220T	685	100S	170T	220T			P46	
HFO	R1234ze(E)	POE	-20°C	325	46S	685		685	1005	170T	220T	685	100S	170T	220T				
HCFO	R1233zd(E)	MO/POE	-20℃					4GS	4GSD	685		4GS	4GSD	685					

	MO	SUNISO 3GS	мо	SUNISO 4SA	POE	Sunice SL-10S	POE	Sunice SL-120T	PAG	Sunice P4
		SUNISO 4GS		SUNISO 4HT		Sunice SL-22S		Sunice SL-170T		Sunice Pl
ISO'S Products		SUNISO 5GS				Sunice SL-32S		Sunice SL-220T		
J30 3 Houdets		SUNISO 3GSD				Sunice SL-46S		Sunice SL-320T		
		SUNISO 4GSD				Sunice SL-68S	POE	Sunice SL-68SP		
		SUNISO 5GSD				Sunice SL-100S				

2 P46 2 PB100 MO :Mineral POE:Polyolesters PAG:Polyalkylene glycols



SUNI

3GS

Package

.	Drum	Pails		CARTON CASE	
	200L	20L	$4L \times 6$	$1L \times 10$	$1L \times 12$
SUNISO GS/GSD	\checkmark	\checkmark	\checkmark		
SUNISO 4SA/4HT	\checkmark	\checkmark			
Sunice SL	\checkmark	\checkmark	\checkmark	\checkmark	
Sunice SL-68SP		\checkmark		\checkmark	
Sunice P46				\checkmark	
Sunice PB100	\checkmark				\checkmark

SUNISO 3GS SUNISO

Notes



	_	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			 -	-	-	-	-		 	,
-	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_		_	 _	_	_	_	_		 	
		_	_	_	_	-	-	_	_	-	-	-	-	_	-	_	_	_	_	_	_	-	-	-	-	_			 _	-	-	_	_		 	
	_	_	-	-	-	-	-	_	_	-	-	-	-	-	-	_	-	-	-	-	-	_	-	-	-	-			 _	-	-	-	-		 	
	_	_	-	_	_	-	-	_	_	_	_	-	-	-	-	_	_	_	_	_	_	-	-	-	-	_			 _	_	-	-	_		 	
	_	_	_	-	-	-	-	-	_	_	-	-	-	-	-	_	_	_	-	-	-	-	-	-	-	_			 _	-	-	-	-		 	
	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_			 _	_	_	_	_		 	
	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_			 _	_	_	_	_		 	
-	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_			 _	_	_	_	_		 	
_	_	_	_	_	_	_	-	-	-	_	_	_	_	_	_	_	_	_	_	_	_	-	_	_	_	_			 _	-	_	_	_		 	
-	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_			 _	_	_	_	_		 	
	_	_	_	_	_	-	_	_	_	_	_	_	_	_	_	_	-	-	-	-	-	_	-	-	-	_			 _	_	_	_	_		 	
-	_	_	-	_	-	_	_	_	_	_	_	_	_	-	_	_	_	_	_	_	_	_	_	_	_	-			 _	_	_	_	_		 	
-	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_			 _	_	_	_	_		 	
	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_		 	_	_	_	_	_		



Contact:

EastAsia, Austraria & New Zealand Japan Sun Oil Company, Ltd.

Trusty Kojimachi Bldg., 3-4 Kojimachi, Chiyoda-ku,Tokyo 102-0083 exp@sunoco.co.jp www.sunoco.co.jp

SouthEast Asia & India SUNOCO (THAILAND) Co., Ltd.

United Tower 15th Floor,333/21 Sukhumvit Rd,Soi 55,North Klongton,Wattana, Bangkok 10110 Thailand exports@sunoco.co.th www.sunoco.co.th