



BRILL® Mixed Viscosity Table

17.5W-50 × 20W-60

17.5W-50	20W-60	Viscosity(40°C)	Viscosity(100°C)	Mixed Viscosity Grade
100%	0%	142.9	20.1	17.5W-50
95%	5%	144.6	20.3	17.5W-50
90%	10%	146.4	20.5	17.5W-50
85%	15%	148.2	20.7	17.5W-50
80%	20%	150.0	20.9	17.5W-50
75%	25%	151.8	21.1	20W-50
70%	30%	153.7	21.3	20W-50
65%	35%	155.5	21.5	20W-50
60%	40%	157.4	21.7	20W-55
55%	45%	159.4	21.9	20W-55
50%	50%	161.3	22.1	20W-55
45%	55%	163.3	22.3	20W-55
40%	60%	165.3	22.5	20W-55
35%	65%	167.3	22.7	20W-55
30%	70%	169.3	22.9	20W-55
25%	75%	171.4	23.1	20W-55
20%	80%	173.5	23.4	20W-60
15%	85%	175.6	23.6	20W-60
10%	90%	177.7	23.8	20W-60
5%	95%	179.9	24.0	20W-60
0%	100%	182.1	24.3	20W-60

Unit for Viscosity mm²/S